
MONTANA FISH, WILDLIFE & PARKS

COONEY STATE PARK SHORELINE STABILIZATION COTTONWOOD CAMPGROUND

near Roberts, MT

#7196128



Location

North

Project Location

Vicinity Map

MONTANA FISH, WILDLIFE AND PARKS DESIGN AND CONSTRUCTION

MAILING ADDRESS: PO BOX 200701

PHYSICAL ADDRESS: 1522 9th AVENUE


HELENA, MT 59620-0701 HELENA, MT 59601

TEL 406.841.4000 FAX 406.841.4004

fwp.mt.gov/Doing Business/Design&Construction

DRAWING INDEX

| Sheet Number | Sheet Title |
|--------------|----------------|
| 1 | COVER SHEET |
| 2 | SITE PLAN |
| 3 | DETAIL SHEET I |




| P. Jagoda | 7/23/20 | | |
|-------------|---------|--------------|-------|
| DRAWN BY: | DATE: | APPROVED BY: | DATE: |
| P. Jagoda | 7/23/20 | | |
| CHECKED BY: | DATE: | APPROVED BY: | DATE: |


DATE: APPROVED BY APPROVED BY

Location Map



Cover Sheet MONTANA FISH, WILDLIFE & PARKS Cooney State Park - Shoreline Stabilization Cottonwood Campground





FLEXAMAT® INFORMATION

Website:

Manufacturer: Motz Enterprises, Inc. Product Name: Flexamat

Address: 3153 Madison Road

Cincinnati, Ohio 45209 513-772-6689 Telephone: 513-772-6690 Fax: Info@Flexamat.com Fmail:

www.Flexamat.com

CONSTRUCTION NOTES:

- CONTRACTOR SHALL CONTACT FLEXAMAT FOR ROLL LENGTH TAKEOFFS AND GEOGRID EXTENSIONS ON ROLLS PRIOR TO ORDERING MATERIAL.
- 2. PERFORM GRADING FOR A UNIFORM SUBGRADE. ALL SUBGRADE SURFACES PREPARED FOR PLACEMENT OF MATS SHALL BE SMOOTH AND FREE OF STICKS, ROOTS, OR DEBRIS OF ANY KIND. THE PREPARED SURFACE SHALL PROVIDE A FIRM UNYIELDING FOUNDATION FOR THE MATS.
- 3. PRIOR TO INSTALLING THE FLEXAMAT, INSTALL 10 OZ. NON-WOVEN GEOTEXTILE OVER SLOPES IN OPPOSITE DIRECTION OF FLEXAMAT (e.g. HORIZONTAL ALONG SLOPE CONTOURS). OVERLAP SEAMS OF GEOTEXTILE MIN. 24-INCHES.
- 4. INSTALL FLEXAMAT ROLLS THAT ARE 15.5' WIDE AND INCLUDE A 12" GEOGRID EXTENSION FOR OVERLAPPING MATS. THE TOP EDGE OF MAT SHALL BE ANCHORED 18" VERTICALLY IN ANCHOR TRENCH. INSTALL SUBSEQUENT MATS OVER THE 8" GEOGRID EXTENSION OF THE PREVIOUSLY INSTALLED ADJACENT MAT. MATS SHALL BE CONTINUOUS SECTIONS FROM TOP TO BOTTOM WITH NO SEAMS.
- 5. SECURE OVERLAP SEAMS IN 2 FT. INCREMENTS USING STAINLESS STEEL ZIP TIES. ZIP TIES SHALL ENCAPSULATE 3 CORDS OF GRID OF BOTH THE TOP MAT AND THE GEOGRID EXTENSION FROM ADJACENT MAT.
- 6. AT THE TOP AND BOTTOM ANCHOR TRENCHES, EMBED THE MAT THE REQUIRED DEPTH (18" & 24"), FILL AND COMPACT WITH
- 7. INFILL THE FLEXAMAT WITH SOIL AS INDICATED ABOVE THE REQUIRED ELEVATIONS UP TO THE PARKING AREA AND SEED OVER THE INFILL WITH SITE SPECIFIC SEED BLEND, FERTILIZER AND EROSION CONTROL BLANKET.

| P. Jagoda | 7/23/20 | |
|-------------|---------|-----------|
| DRAWN BY: | DATE: | REVIS |
| P. Jagoda | 7/23/20 | |
| CHECKED BY: | DATE: | APPRO |
| | | |

| REVISED BY: DATE: | APPROVED BY: | DATE: |
|--------------------|--------------|-------|
| APPROVED BY: DATE: | APPROVED BY: | DATE: |

